



Short-Throw Projectors

MW824ST

Advancing a Brighter, Greener Future the SmartEco™ Way

Conserve energy, increase lamp life and all the while enjoy an exceptional visual performance with BenQ's SmartEco technology



Unparalleled Efficiency, Performance and Readiness with BlueCore™

With the next-generation laser light source, BlueCore sets new standards of projector performance for classroom projectors





PT. MANDIRI ARTHA SOLUSI
EMPOWERING BUSINESS FORWARD



MW824ST

Short-Throw Projector

Technical Specification

Projection System	DLP™ Digital Optical Processing Projection Technology
Native Resolution	WXGA (1280X800)
Brightness (ANSI Lumens)	3200 ANSI Lumens
Contrast Ratio	13000:1
Display Color	1.07 Billion Colors
Lens	F= 2.8, f = 7.51mm
Throw Ratio	0.52 (95" @ 1m)
Image Size (Diagonal)	Optimization 72"-152", Maximum 300"
Zoom Ratio	Fixed
Lamp Type	210W
Lamp Mode (Normal/Economic)	4000/5000/6500/10000/4000(with 2100 of constant brightness) hours
Keystone Adjustment	1D, Vertical ± 30 degrees
Projection Offset	110% ± 5%
Resolution Support	VGA (640 x 480) to UXGA (1600 x 1200)
Horizontal Frequency	15-102KHz
Vertical Scan Rate	23-120Hz
HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility	Frame Sequential: Up to 720p Frame Packing: Up to 1080p Side by Side: Up to 1080i/p Top Bottom: Up to 1080p
Interface	Computer in (D-sub 15pin) (Share with component) Monitor out (D-sub 15pin), HDMI USB (Type Mini B), Composite Video in (RCA), S-Video in (Mini DIN 4pin), Audio in (Mini Jack) Audio out (Mini Jack), Audio L/R in (RCA), Speaker (10W), USB (Type Mini B), RS232 (DB-9pin), LAN (RJ45)
Audible Noise (Normal/Economic Mode)	33/28 dBA (Normal/Economic mode)
Picture Modes	Dynamic/Presentation/sRGB/Cinema/(3D)/User 1/User 2
Power Supply	AC100 to 240 V, 50 to 60 Hz
Power Consumption	Normal 290W, Eco 240W, Standby <0.5W

Contact Us.

(021) 22813394 info@mandiriarthasolusi.co.id